6

7

8

9

10

11

12

13

14

15

16

17

18

19

26

27

A magnetic head comprising: an electrical contact pad; a substrate on which the magnetic head is formed; and a material selected to have a low dielectric constant interposed between the pad and the substrate.

The magnetic Head of claim 1, wherein the low dielectric material is configured to decrease the parasitic capacitance of the magnetic head.

- 3. The magnetid head of claim 1, further comprising a stud formed through the low dielectric material.
 - The magnetic head of claim 3, wherein the stud comprises Cu. 4.
- The magnetic head of claim 3, wherein the stud comprises a conductive 5. material.

The magnetic head of claim 1, wherein the low dielectric material comprises hard-bake photo resist.

- 7. The magnetic head of claim 1, wherein the low dielectric material comprises SiO₂.
- 8. The magnetic head of claim 1, wherein the low dielectric material has a thickness in a range of between about 1 μm and about 100 μm.

9. The magnetic head of claim 1, wherein the low dielectric material has a thickness in a range of between about 10 μm and about 50 μm .

10. The magnetic head of claim 1, wherein the low dielectric material has a thickness of about 20 μm .

11. The magnetic head of claim 1, wherein the low dielectric material has a dielectric constant of less than about 9.

12. The magnetic head of claim 1, wherein the low dielectric material has a dielectric constant of about 3.

13. The magnetic head of claim 1, wherein the magnetic head carries a GMR sensor.

14. The magnetic head of claim 1, wherein the low dielectric material provides a platform for the electrical contact pad.

The magnetic head of claim 1, wherein an electrical contact pad having a surface area of less than about 20 μm in order to reduce capacitance coupling with the substrate.

27

Swk () X
teel gering gering gering every towng every seeing gering gering towng gering towng	
LER	E 425 !4101

6

7

8

0

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

BRIAN C. KUNZLER ATTORNEY AT LAW 10 WEST 100 SOUTH, SUITE 425 SALT LAKE CITY, UTAH 84101

16.	A reduced capacitance magnetic head comprising:
	an electrical contact pad;
	a substrate on which the magnetic head is formed;
	a conducting layer formed over the substrate;

a low dielectric material interposed between the pad and the substrate which is used as a platform for the electrical contact pad to increase the distance between the substrate and the electrical contact pad, the low dielectric material comprising hard bake photo resist and having a thickness of about 20 μ m and a dielectric constant of about 3; and

a conducting stud formed through the low dielectric material to make electrical connection between the electrical contact pad and the conducting layer.

17. A disk drive system, comprising:

a reduced capacitance magnetic head comprising:

an electrical contact pad;

a substrate on which the magnetic head is formed;

a material selected to have a low dielectric constant interposed between the pad and the substrate; and

a magnetic recording disk;

a spin-valve sensor for reading data recorded on the recording disk; and an actuator for moving the spin valve sensor across the magnetic recording disk in order for the spin-valve sensor to access different magnetically recorded data on the magnetic recording disk; and

a detector electrically coupled to the spin-valve sensor and configured to detect changes in resistance of the sensor caused by rotation of the magnetization of the sensing layer relative to the fixed magnetizations of the pinned layer in response to changing magnetic fields induced by the magnetically recorded data.

And the true and made the true to the true true true true true true true tru	
BRIAN C. KUNZLER Attorney at law 10 west 100 south, suite 425 Salt lake city, utah 84101	

18. The disk drive system of claim 17, further comprising a stud formed through the low dielectric material.

- 19. The disk drive system of claim 17, wherein the low dielectric material is configured to decrease the parasitic capacitance of the magnetic head.
- 20. The disk drive system of claim 17, wherein the low dielectric material has a thickness in a range of between about 10 μ m and about 50 μ m.
- The disk drive system of claim 17, wherein the magnetic head comprises a GMR sensor.
 - 22. A reduced capacitance magnetic head comprising:

 a substrate on which the magnetic head is formed; and
 a contact pad disposed above the substrate and having a surface area less
 than about 20 µm in order to reduce capacitance coupling with the
 substrate.
 - 23. A magnetic head comprising:

 a substrate on which the magnetic head is formed;

 an alumina undercoat layer comprising Al₂O₃ formed over the substrate;

 an electrical contact pad; and

 a layer of alumina interposed between the electrical contact pad and the alumina undercoat layer.

	2
181	_
July.	\ ⁴
$\sim c u_{\ell}$)\' ₅
V	6
	7
	8
in the	9
	10
	11
	12
M.	13
Harth Alexandra Andrewson Thomas Thomas	14
	15
alle Hall Kar	16
# *±#	17
	18
	19
	20
LER re 425 84101	21
UNZ AT LAW FH, SUN , UTAH	22
BRIAN C. KUNZLER ATTORNEY AT LAW 10 WEST 100 SOUTH, SUITE 425 SALT LAKE CITY, UTAH 84101	22232425
LAN ATTC WEST 19 LT LAK	24
BR 10 SA	25

27

24. A magnetic head comprising:

a substrate on which the magnetic head is formed;

an alumina undercoat layer comprising SiO₂ formed over the substrate;

an electrical contact pad; and

a layer of alumina interposed between the electrical contact pad and the alumina undercoat layer.

25. A method of reducing capacitance in a magnetic head, comprising:

providing a substrate;

providing a read/write head; and

isolating the read/write head from the substrate in order to reduce the capacitance coupling between the read head and the substrate.